

SIEMENS

Ingenuity for life

Pointek CLS300

Hot levels, harsh conditions


usa.siemens.com/level

Inverse frequency shift capacitance level switch

In harsh process conditions with high chemical and physical abuse, reliability and accuracy are critical for safe and economical operation. For these conditions, Pointek CLS 300 is the ideal level switch. It is used for high and low level alarm of interfaces, solids, liquids, slurries and viscous materials. This capacitance switch handles temperatures up to 400 °C (752 °F) and pressures from full vacuum to 35 bar g (511 psi g). Pointek CLS 300 applies a unique approach to capacitance technology that is based on extensive field experience. It includes patented Active-Shield and Inverse Frequency Shift technology, ensuring high accuracy, resolution and repeatability.

- Inverse Frequency Shift capacitance technology results in higher accuracy and resolution.
- Patented Active Shield provides superior reliability.
- Tank walls, variations in product quality, vapor and dust have a negligible effect on the readings.
- Automated Sensor Test program tells you if circuitry and sensor are fully functional; no need to remove the unit from the tank.
- Online commissioning of parameters allows for full advantage of sensitivity and accuracy of the instrument: number of counts, setpoints, adjustable hysteresis, time delay, and output status. You can make adjustments from the control room or other remote locations.
- A wide range of models are available: rod and cable sensors up to 25 meters (82 ft); high temperature up to 400 °C (752 °F); intrinsically safe and explosion proof.





Pointek CLS300	Standard	Digital
----------------	----------	---------

Power		
	<ul style="list-style-type: none"> • 12 to 250 V AC/DC, 0-60 Hz, galvanically isolated 2W 	<ul style="list-style-type: none"> • Standard: 12 to 30 V DC; 12.5 mA • Intrinsically safe: 12 to 24 V DC, 12.5 mA max.

Interface		
Configuration	Locally using dip switches and potentiometers	<ul style="list-style-type: none"> • Remotely using SIMATIC PDM • Locally using 3 button keypad (stand alone)
Display	Transmitter with 3 LED indicators	Local digital LCD display
Communication		<ul style="list-style-type: none"> • PROFIBUS PA (IEC 61158 CPF3 CP3/2) • Bus physical layer: IEC 61158-2 MBP(IS) • Device profile: PROFIBUS PA profile for Process Control Devices Version 3.0, Class B • FISCO field device
Output	<ul style="list-style-type: none"> • Relay: 1 SPDT Form C relay • Solid state switch • Time delay: (ON and/or OFF) 1 to 60 s • Fail-safe operation (high or low) 	<ul style="list-style-type: none"> • Solid state switch: galvanically isolated • Time delay: (ON and/or OFF) programmable by user • Fail-safe operation (high or low)

Mechanical		
Enclosure	<ul style="list-style-type: none"> • Powder-coated aluminium with gasket • Optional thermal isolator, 316 stainless steel (1.4404) • Type 4/NEMA 4/IP65, IP68 optional 	
Process connection	316 stainless steel (1.4404) (standard and cable)	
Sensor	<ul style="list-style-type: none"> • PFA (standard), stainless steel (1.4404) (cable), 316L and PEEK (high temperature) • Max. 1 m (40") standard and high temperature • Max. 25 m (82 ft); stainless steel with FEP coating (cable) 	

Process conditions		
Ambient temperature	-40 to 85 °C (-40 to 185 °F)	
Process temperature	<ul style="list-style-type: none"> • -40 to 200 °C (-40 to 392 °F) • -40 to 400 °C (-40 to 752 °F) 	
Pressure*	-1 to 35 bar g (-14.6 to 511 psi g)	-1 to 35 bar g (-14.6 to 511 psi g)
Dielectric constant &	Min. 1.5	

Approvals		
	CE, CSA, FM, ATEX, WHG Overfill Protection (Germany), Lloyd's Register of Shipping Categories ENV1, ENV2, and ENV5, Pattern Approval (China), C-TICK (Australia), SIL 2 (Overspill)	

Siemens Industry, Inc.
 100 Technology Drive
 Alpharetta, GA 30005
 1-800-365-8766
 info.us@siemens.com

Subject to change without prior notice.
 Order No.: PIFL-5EW03-1016
 All rights reserved
 Printed in the USA
 © 2016 Siemens Industry, Inc.

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

Pointek is a registered trademark of Siemens Milltronics Process Instruments Inc.
 * Pressure is temperature dependent. SIMATIC PDM is a registered trademark of Siemens.
 © 2016 Siemens Milltronics Process Instruments Inc.