

Production Testing Information for Series J

usa.siemens.com/distribution-transformers

Each low-voltage transformer is tested

Ratio:

The ratio of the number of turns in a higher voltage winding to that in a lower voltage winding. This test confirms the ratio of input voltage to output voltage is correct.

Core Loss:

Evaluation of no load wattage at rated primary voltage to confirm the core loss. This test confirms the unit meets design requirements.

Hi-Pot:

Abbreviation for "high potential," used to verify electrical insulation in finished transformers. This test checks for electrical shorts.

Induced:

Checks the insulation between turns, layers and sections of a winding. This test checks for electrical shorts.

Polarity:

To check the alignment or orientation of a circuit in relation to the parallel or banking of transformers. This test checks that the primary and secondary phase relations are correct.

Optional low-voltage tests

Temperature Rise:

Unit tested to point of steady temperature condition to confirm that it meets required temperature rise.

Sound Level:

Background noise level measured and unit powered at rated voltage and frequency under no-load conditions to confirm unit meets NEMA ST-20 requirements.

Full Load Losses:

Test of load carried by transformer at a specific frequency.

Impedance:

Test measures the opposition to time-varying electric current in an electric circuit.

Efficiency:

Running different load tests to confirm unit meets efficiency requirements of DOE or CSA802.



Certified test reports can be provided upon request.

Note: Additional costs apply for all optional testing and certified testing.

Source: Definitions of IEEE Standard Test Codes

Transformer testing medium-voltage

Each medium-voltage transformer is tested

DC Resistance:

Measurement of DC resistance using a resistance bridge.

Voltage Ratio (Turns Ratio):

Verification of the turns ratio conforms to design.

Impedance:

The shorting of one winding and voltage is applied to the other winding. Losses, voltage and current is measured.

Applied Voltage:

60 Hz is applied to the winding voltage. Voltage is then applied for one minute to the winding while core and other winding are grounded.

Induced Voltage/Load Loss:

2X rated voltage between terminals of a winding while all other terminals are open.

No Load Loss / Excitation Current:

Rated voltage is applied to winding, the current and losses are measured.

Dialectric:

Determines if transformer complies with "over-voltage" requirements.

Polarity/Phase-Relation:

Determines angular displacement and phase sequence as compared to specification.

Electric & Magnetic Field (EMF):

Measures Electric and Magnetic fields produced by the transformer.

Published by Siemens 2019

Siemens Industry, Inc. 5400 Triangle Parkway Norcross, GA 30092

Siemens Technical Support: 1-800-333-7421 info.us@siemens.com

Printed in USA-CP Order No. PDFL-TFTEST-1119 All Rights Reserved © 2019, Siemens Industry, Inc. usa.siemens.com/distribution-transformers

The technical data presented in this document is based on an actual case or on as-designed parameters, and therefore should not be relied upon for any specific application and does not constitute a performance guarantee for any projects. Actual results are dependent on variable conditions. Accordingly, Siemens does not make representations, warranties, or assurances as to the accuracy, currency or completeness of the content contained herein. If requested, we will provide specific technical data or specifications with respect to any customer's particular applications. Our company is constantly involved in engineering and development. For that reason, we reserve the right to modify, at any time, the technology and product specifications contained herein.

Optional medium-voltage tests

Temperature Rise:

Verification the temperature of the transformer "hot spot" over ambient temperature complies to the specification/ nameplate rating.

Sound Level:

Measures the sound emitted by the transformer.

Short Circuit:

Confirms the mechanical capability of a transformer can withstand a system short circuit.

BIL Level

Determines the ability of the insulation system to withstand a lightning induced voltage surge.

Partial Discharge:

Tests the integrity of the insulation and the capability to withstand partial discharge.



Certified test reports can be provided upon request.

Note: Additional costs apply for all optional testing and certified testing.

Source: Definitions of IEEE Standard Test Codes