

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type: 0AV3112A

SIMOTICS FL - 112 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe area

U	Δ / Y	f	P	P	I	n	M	η			cos φ			I <sub>A</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub>	M <sub>K</sub> /M <sub>N</sub>	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I <sub>I</sub> /I <sub>N</sub>	T <sub>I</sub> /T <sub>N</sub>	T <sub>B</sub> /T <sub>N</sub>	
400	Δ	50	4	-	7.3	2925	13.1	88.1	89.6	89.8	0.9	-	-	7.8	2.6	3.6	IE3
690	Y	50	4	-	4.20	2925	13.1	88.1	89.6	89.8	0.9	-	-	7.8	2.6	3.6	IE3
IM B3			FS 112 M		IP 55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN								

Environmental conditions : -20°C - +40°C / 1000 m

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	62 / 74 dB(A)	- / -	Vibration severity grade	A
Moment of inertia	0.00879 kg m2		Insulation	155(F) to 130(B)
Bearing DE   NDE	6206 2Z C3	6206 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L <sub>10mh</sub> , F <sub>Rad min</sub> for coupling operation 50 60Hz	20000 h	-	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	36 kg
Regreasing device	no		Coating (paint finish)	Standard paint finish C2
Grease nipple			Color, paint shade	RAL7030
Type of bearing	floated bearing DE and NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	no		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	no			

Terminal box

Terminal box position	top	Cable diameter from ... to ...	18 mm - 25 mm
Material of terminal box	aluminum	Cable entry	M32 x 1.5 + M32 x 1.5
Type of terminal box	-	Cable gland	2 glands
Contact-screw thread	M4		
Max. cross-sectional area	4 mm2		

Special design

--	--	--	--

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
SIEMENS	document type datasheet			document status released		customer		
	title 1LE0323-1BA23-4AA4			document number				
	© SIEMENS AG 2022			rev. 01	creation date		language en	page 1/2



# Efficiency documentation for 50/60Hz three-phase Squirrel-Cage-Motors SIMOTICS

MLFB: 1LE0323-1BA23-4AA4


Motortype: 0AV3112A

motor rating						
U <sub>N</sub> [V]	Δ / Y	f <sub>N</sub> [Hz]	P <sub>N</sub> [kW]	I <sub>N</sub> [A]	n <sub>N</sub> [1/min]	T <sub>N</sub> [Nm]
400	Δ	50	4	7.3	2925	13.1

## Power losses acc. to COMMISSION REGULATION (EU) 2019/1781

operating point (n:T)	losses P <sub>L</sub> [W]	relative losses P <sub>L</sub> /P <sub>N</sub> [%]
P <sub>1</sub> (90:100)	491	12.3
P <sub>2</sub> (50:100)	428	10.7
P <sub>3</sub> (25:100)	393	9.8
P <sub>4</sub> (90:50)	197	4.9
P <sub>5</sub> (50:50)	153	3.8
P <sub>6</sub> (50:25)	85	2.1
P <sub>7</sub> (25:25)	63	1.6


## Map of losses - relative losses P<sub>L</sub>/P<sub>N</sub> [%]



### Notes / Definitions

T as relative T: T/T<sub>N</sub> [%]

n as relative n: n/n<sub>N</sub> [%]

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE0323-1BA23-4AA4							document number
© SIEMENS AG 2022		rev. 01	creation date		language en	page 2/2		