

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type: 0CV3182A

SIMOTICS FL - 180 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	4/4	η 3/4	2/4	cos φ 4/4	3/4	2/4	I _A /I _N I _f /I _N	M _A /M _N T _f /T _N	M _K /M _N T _B /T _N	IE-CL
400	Δ	50	22	-	38.5	2950	71	92.7	93	92.4	0.89	-	-	7.8	2.4	3.4	IE3
690	Y	50	22	-	22.5	2950	71	92.7	93	92.4	0.89	-	-	7.8	2.4	3.4	IE3
IM B3			FS 180 M		IP 55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN								

Environmental conditions : -20°C - +40°C / 1000 m

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70 / 83 dB(A)	- / -	Vibration severity grade	A
Moment of inertia	0.077 kg m ²		Insulation	155(F) to 130(B)
Bearing DE NDE	6210 Z C3	6210 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} , F _{Rad min} for coupling operation 50 60Hz	20000 h	-	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	171 kg
Regreasing device	no		Coating (paint finish)	Standard paint finish C2
Grease nipple			Color, paint shade	RAL7030
Type of bearing	floated bearing DE and NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	no		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	no			

Terminal box

Terminal box position	top	Cable diameter from ... to ...	22 mm - 32 mm
Material of terminal box	cast iron	Cable entry	M40 x 1.5 + M40 x 1.5
Type of terminal box	-	Cable gland	2 glands
Contact-screw thread	M5		
Max. cross-sectional area	16 mm ²		

Special design

--	--	--	--

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
SIEMENS	document type datasheet			document status released		customer	
	title 1LE0023-1EA23-4AA4			document number			
	© SIEMENS AG 2022			rev. 01	creation date	language en	page 1/2

Efficiency documentation for 50/60Hz three-phase Squirrel-Cage-Motors SIMOTICS

MLFB: 1LE0023-1EA23-4AA4


Motortype: 0CV3182A

motor rating						
U _N [V]	Δ / Y	f _N [Hz]	P _N [kW]	I _N [A]	n _N [1/min]	T _N [Nm]
400	Δ	50	22	38.5	2950	71

Power losses acc. to COMMISSION REGULATION (EU) 2019/1781

operating point (n:T)	losses P _L [W]	relative losses P _L /P _N [%]
P ₁ (90:100)	1664	7.6
P ₂ (50:100)	1261	5.7
P ₃ (25:100)	1080	4.9
P ₄ (90:50)	818	3.7
P ₅ (50:50)	516	2.3
P ₆ (50:25)	332	1.5
P ₇ (25:25)	208	0.9


Map of losses - relative losses P_L/P_N [%]



Notes / Definitions

T as relative T: T/T_N [%]

n as relative n: n/n_N [%]

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet		document status released		customer			
	title 1LE0023-1EA23-4AA4		document number					
© SIEMENS AG 2022			rev. 01	creation date	language en	page 2/2		