

# Technical datasheet

## SIMOTICS CONNECT 400

[siemens.com/digital-motor](https://siemens.com/digital-motor)



General information	
Product brand name	SIMOTICS CONNECT 400
Hardware version	Feature State FS04
Product category	Sensor and communication module
Product description	SIMOTICS CONNECT 400 with integrated sensors monitors the condition of the motor to make its operation transparent, which facilitates application and process optimizations. SIMOTICS CONNECT 400 can be used in conjunction with the MindSphere app SIDRIVE IQ Fleet only.
Monitoring application	Visualization of motor health status and data analytics based on digital motor twins are offered in the comprehensive SIDRIVE IQ Fleet MindSphere app.
Measured motor parameters	Temperature, radial/tangential/axial vibration, electrical stator frequency, slip frequency
Calculated motor parameters	Motor state (on/off), rotation speed, torque, electrical power, number of motor starts, energy consumption, energy cost, CO <sub>2</sub> emission, energy efficiency, hours of operation, operating points based on speed-load-vibration profiles
Extended monitoring and maintenance support	External noise cancelling via peak detection for vibration monitoring (cross check with ISO 10816), anomaly and failure detection and warning system based on detected operating points and machine fingerprints, automatic warning system for maintenance actions, bearing condition monitoring with traffic light function (incl. bearing status signal).
Supported motors	Fin-cooled, 3-phase asynchronous low-voltage motors in line operation (DOL) and converter operation (VSD), IEC frames sizes 80 to 450 and NEMA frame sizes 48 to 680
Installation/mounting	
Mounting type and position	Externally mounted on the motor's cooling fins with a mounting bracket (glued). <i>As described in the installation instructions</i>
Qualified adhesives	Henkel LOCTITE® HY 4090™, Weicon Fast Metal Minute Adhesive, 3M Scotch-Weld DP 8407 NS
Power supply	
Type of supply	Battery pack (Li/SOCl <sub>2</sub> , 3.6 V, 3 cells size AA, plus HLC, non-rechargeable).
Battery lifetime	Operating time up to 2 years*, replaceable for lifetime extension *At an environmental temperature of 0° C to 40° C, a measurement interval of 5 minutes and a transmission of the stored data once every 24 hours
Internal data storage	
Internal flash	Data storage of min. 48 hours*, when MindSphere connection is interrupted *At measurement interval of 1 minute

<b>Communication</b>	
<b>Bluetooth®</b>	Used for configuration and commissioning*, Compliance with Bluetooth® v4.1 Frequency: 2402 MHz to 2480 MHz, Range: up to 10 m <i>* Commissioning consists of integration into the local WLAN network and onboarding to MindSphere</i>
<b>WLAN</b>	Used for data transmission* and firmware updates, IEEE 802.11 b/g/n Frequency: 2400 MHz to 2483.5 MHz, Range: up to 100 m <i>* MindSphere synchronization interval adjustable between 1 hour and 48 hours (default: 24 hours)</i>
<b>Status information</b>	
<b>Indication LED (blue)</b>	Status information during configuration process
<b>Integrated sensors</b>	
<b>Measurement interval</b>	Configurable between 1 minute and 1 hour (default: 5 minutes)
<b>Temperature measurement</b>	
<b>Range</b>	–40° C to +85° C
<b>Resolution</b>	0.03° C <i>Temperature measured at the contact between connectivity module and mounting bracket</i>
<b>Vibration measurement</b>	
<b>Physical measuring principle</b>	Overall vibration $V_{RMS}$ 3-axis
<b>Range</b>	0.02 to 180 mm/s Standard measurement: 10 Hz to 1.6 kHz (Sampling rate: 3.3 kHz); Performance measurement for daily detailed health check: 10 Hz to 3.3 kHz (Sampling rate: 6.6 kHz, for measurement intervals $\geq 5$ min)
<b>Magnetic field measurement</b>	
<b>Range</b>	0.01 Hz to 300 Hz Rotary stray field
<b>Standards, approvals, certificates</b>	
CE, FCC, IC, SRRC, RCM, ETA, SDPPI, ICASA, SUBTEL, ARCOTEL, MTC, FAC, CNC, CRC, NBTC, IMDA, OFCA, MOC, KVALITET, ICT, SIGET, IFT, CERT	
<b>Degree and class of protection</b>	
<b>Degree of protection acc. to EN 60529</b>	IP65
<b>Shock resistance</b>	max. 100 m/s <sup>2</sup> (tested acc. class 3M4)
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	–40° C to +80° C
<b>Ambient temperature during storage/ transportation</b>	–20° C to +40° C
<b>Relative humidity</b>	5% to 95% (without condensation)
<b>Software</b>	
<b>Mobile app for commissioning and configuration</b>	SIDRIVE IQ Config (iOS, Android)
<b>SIMOTICS CONNECT Firmware Update</b>	Supports remote firmware update via MindSphere (v0.6.0.0 or newer)
<b>Mechanics/material</b>	
<b>Housing material</b>	Industrial Plastic Durethan® (polyamide, halogen-free, glass-fiber reinforced)
<b>Material of the mounting bracket // screws</b>	stainless steel // steel, galvanized and passivated
<b>Dimensions</b>	
<b>Length x height x depth</b>	125,4 mm x 77,5 mm x 29 mm
<b>Weight</b>	
<b>Weight connectivity module, approx.</b>	0.25 kg
<b>Weight connectivity module including mounting material, approx.</b>	0.50 kg
<b>Documentation and information</b>	
More technical product information and documentation is available at: <a href="http://siemens.com/digital-motor">siemens.com/digital-motor</a>	

**Published by  
Siemens AG**

Digital Industries  
Motion Control  
P.O. Box 31 80  
91050 Erlangen, Germany

For the U.S. published by  
Siemens Industry Inc. 100  
Technology Drive Alpharetta,  
GA 30005 United States

Article-No. DIMC-B10048-02-7600  
Dispo 21400  
Printed in Germany  
WÜ/1000173743 SB 0223 PDF  
© Siemens AG 2023

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract. All product designations may be trademarks or product names of Siemens AG or other companies whose use by third parties for their own purposes could violate the rights of the owners.

For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>