



MODULE LABEL KEY

ANALOGUE MODULE	AN 1 etc
INPUT/OUTPUT MODULE	I/O 1 etc
P.S.U. & BASIC I/O MODULE	P.S.U.

ABBREVIATIONS

CT	CURRENT INPUTS
VT	VOLTAGE INPUTS
SI	STATUS INPUTS
CO	CHANGE OVER OUTPUT CONTACTS
NO	NORMALLY OPEN OUTPUT CONTACTS
NC	NORMALLY CLOSED OUTPUT CONTACTS

FOR INFORMATION ONLY
UNCONTROLLED COPY
NOT SUBJECT TO UPDATE

MATERIAL:

Dimensions in millimetres ; Surface texture in micrometres.
Machine where marked ✓
For explanation of dimensions, tolerances, notes etc. see B.S.308.
Limit on untoleranced unmachined dimensions ±
Limits on untoleranced machined dimensions to B.S.4500;
i.e. up to 6±0.1; over 30 to 120±0.3; over 315±0.8;
over 6 to 30±0.2; over 120 to 315±0.5;
General unmachined angular tolerance ±

Finish:	Title:	First used on:
Treatment:	TERM IDENT & WIRING DIAGRAM FOR IOTA RELAY (4VT,43SI,3CO,42NO) E16 CASE	Similar Articles:
VA TECH Reyrolle AUTOMATION, CONTROL & PROTECTION		Supersedes:
Original Scale: NTS		Drg. No. 2761W11022
DRAWN ML/MM CHECKED RDW APPROVED RD.WATSON DATE 25/2/05 IE OPS PCP Purch.Spec. TQ		EAC CE STD A1

Copyright © 2005 VA TECH Reyrolle Ltd. Hebburn

1	24/02/05	CHANGE
ISSUE	DATE	NOTED