



**SIEMENS**

*Ingenuity for life*




Analytical Products and Solutions



## Detailed Hydrocarbon Analysis


n-Paraffin, i-Paraffin, Naphthenes, Aromatics



One of the most complex analytical tasks in the refinery industry is the detailed hydrocarbon analysis of Naphtha, Reformate or Alkylate. It involves the characterization and quantification of several hundred individual components. Often done in the lab with associated time delay, the MAXUM process gas chromatograph provide that long term repeatable separation and reliable categorization faster and continuous. Providing quantitative results on-line permits tighter process control and therefore improved intermediate and final product quality with potentially very high economic benefits.



[usa.siemens.com/analyticalproducts](http://usa.siemens.com/analyticalproducts)



Chromatogram of Naphtha ranging from C3-C10 hydrocarbons and with an analysis time of 80 minutes.

PINA is the analytical determination of the carbon number distribution of n-Paraffin, i-Paraffin, Naphthenes and Aromatics concentration in Naphtha, Reformate and Alkylate. The Olefins content has to be less than 3%. The analysis is performed according ASTM method D-5134.

Because the number of individual constituents to be separated and quantified between C3 and C10 is a few hundred, a very stable and repeatable analytical system is required.

A defined sample volume is injected with an on-line liquid injection valve. Separation is achieved by a narrow bore capillary column and detection by Flame Ionization Detector. The detector is independently heated to eliminate possible temperature programming impact on the quantification. Retention time stability and therefore correct identification over an analysis time of 80 minutes is continuously monitored and if needed minute carrier gas flow adjustment are done automatically. A "gold standard" chromatogram is stored and utilized as reference. MAXUM process gas chromatograph with dual airbath oven ensures long term repeatable characterization. Categorizing the various components to the molecule groups is automatically done after every analysis.

The turn-key system solution for installation in electrical hazardous plant locations consist of MAXUM with sample system and if needed analyzer cabinet or shelter.

On-line measurement provides continuous and repeatable results with minimum time delay therefore permitting to improve desired composition with higher consistency.

**For more information, please contact:**

Siemens Industry, Inc.  
 5980 West Sam Houston Parkway North  
 Suite 500  
 Houston, TX 77041  
 Phone: 713-939-7400  
 Email: ProcessAnalyticsSales.industry@siemens.com  
 usa.siemens.com/analyticalproducts

Carbon Number	n-Paraffin	i-Paraffine	Naphthene	Aromatic
1	0			
2	0			
3	0.09			
4	0.84	0.23		
5	2.12	1.66	0.29	
6	3.14	4.22	5.3	0.76
7	4.03	3.9	11.78	3.42
8	4.18	4.97	7.46	5.53
9	5.03	5.94	2.98	
C10+	22.13			
Unknowns	0.01			

Summary of constituents according carbon number and molecule category

- ASTM method D-5134
- C3 to C10 hydrocarbons
- Cycle time approximately 80 minutes
- Repeatability 0.1-0.5% RSD per C- number and category
- MAXUM II Process Gas Chromatograph
- Dual oven temperature programmable
- Sample system with fast and analytical loop

Published by  
 Siemens Industry, Inc.  
 Process Automation  
 Process Industries and Drives  
 100 Technology Drive,  
 Alpharetta, GA 30005

1-800-241-4453  
 info.us@siemens.com  
 Subject to change without prior notice  
 Order No.: PIAFL-00068-0618  
 Printed in USA  
 © 2018 Siemens Industry, Inc.  
 usa.siemens.com/analyticalproducts

The technical data presented in this document is based on an actual case or on as-designed parameters, and therefore should not be relied upon for any specific application and does not constitute a performance guarantee for any projects. Actual results are dependent on variable conditions. Accordingly, Siemens does not make representations, warranties, or assurances as to the accuracy, currency or completeness of the content contained herein. If requested, we will provide specific technical data or specifications with respect to any customer's particular applications. Our company is constantly involved in engineering and development. For that reason, we reserve the right to modify, at any time, the technology and product specifications contained herein.