

FOR MIDTJYSKE JERNBANER A/S, DENMARK

Mireo Plus B

Midtjyske Jernbaner

Rail traffic is playing an increasingly important role. In Germany alone, up to ten million people will be traveling by rail every day by the year 2030. Forty percent of Germany's railway network is not electrified. These sections are mainly used by diesel multiple units (DMUs). Due to the rising price of fuel and stricter emissions regulations, the existing DMUs will have to be replaced by more environmentally friendly electric multiple units (EMUs) that operate without an overhead contact line.

Mireo® is already providing answers to the challenges of the future in regional transport. With Mireo, the engineers at Siemens have created an innovative platform for premium-class commuter and regional transport that is at once energy-efficient, flexible, available for quick delivery, and profitable.

Mireo Plus B combines all the benefits of the Mireo platform with a high-performance battery system. Midtjyske Jernbaner A/S has ordered seven Mireo Plus B trains from Siemens Mobility to operate on rail routes without overhead contact lines in the Midtjylland region of Denmark.

siemens.com/mobility

SIEMENS

Interior design

Combined with the attractive design, the construction of the train's interior creates a spacious ambience, coupled with comfort and safety. This is further enhanced by features such as onboard Internet, passenger information systems, as well as safety monitoring systems (CCTV). The cantilevered seating makes it easy and inexpensive to clean the passenger compartment.


Energy savings

In terms of mileage and range, operators now have access to a high-performance, highly efficient vehicle thanks to the use of SiC technology.

Project details

- Passenger compartment with a modern and future-oriented design
- Generous seat spacing
- CO_2-controlled air conditioning system
- Multifunctional multipurpose areas with sufficient space
- Large displays for passenger information
- Jacobs and standard bogies with inside bearings from the SF7500 family
- All entrances have a sliding step

Mireo Plus B



Technical data

Wheel arrangement	Bo' 2' Bo'
Track gauge	1,435 mm
Maximum speed	140 km/h
Traction power	1,700 kW
Starting acceleration	up to 1.1 m/s^2
Power supply	1 kV or 25 kV AC
Length (over coupling)	46,560 mm
Entrance height	610 mm
Passenger capacity	127 seats
Maximum axle load	< 20 t
Crashworthiness	TSI and EN 15227-compliant
Fire protection	According to EN 45545

Published by
Siemens Mobility GmbH

Otto-Hahn-Ring 6
81739 Munich
Germany

contact.mobility@siemens.com

Printed in Germany
TH S62-240338 DA 0824

Mireo® is a registered trademark of Siemens Mobility GmbH. Any unauthorized use is prohibited. All other designations in this document may represent trademarks whose use by third parties for their own purposes may violate the proprietary rights of the owner.

Subject to changes and errors.
The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

SIEMENS