

# Energy data recording with SIMATIC ET 200SP and SIMATIC S7-1200 energy meters

### No efficiency without transparency

New legal regulations and rising energy prices are persuading a growing number of companies to address the issue of energy management. In order to reduce the demand for energy and the associated costs, it is necessary to find answers to the following questions: Which systems need how much energy and when do they need it? Where do peak loads occur? Which forms of energy have to be optimized? The precise recording of all energy flows is the basis for all energy management in accordance with ISO 50001.

### Space-saving and flexible in use

The Energy Meter is the ideal first step into machine-level energy management and the recording of electrical variables. The measuring device is available in two designs. With being extremely compact, it saves a considerable amount of space in the control cabinet. In addition, it has an convincingly low purchase price and offers a high number of available measured values.

# Get your machine ready for energy management

With the Energy Meter, you get a clearer picture of the electrical energy consumption of your machine in various different operating states. The energy data is captured directly at the machine and can be visualized by means of SIMATIC HMI. This means that machine operators always have the energy behavior under their control and are able to influence the operating behavior immediately. They can, for example, shut down the machine during breaks in production in order to avoid consumption of energy while the plant is at a downtime. Any changes can be quickly identified and associated faults cleared to ensure efficient operation of your machines.

### Technical data **SIMATIC S7-1200** SIMATIC ET 200SP AI SM 1238 Energy Meter 480V Al Energy Meter 480V ST Application One, two and three-phase power supplies of up to 480 V (and higher voltages via voltage converters) Energy meters with a high precision of +/-0.5% with an update time of just 50 ms for: voltage, current, Measured variables power, phase angle, energy/electrical energy, frequency, minimum and maximum values, power factor, operating hours Diagnostics Per phase Per phase or freely adjustable by user for overand undervoltage, overload, tolerance value and tolerance time. Communication PROFINET or PROFIBUS Module width 20 mm 45 mm Number of modules per CPU Up to 8 modules Up to 64 modules Order number 6ES7238-5XA32-0XB0 6ES7134-6PA20-0BD0

#### Your advantages at a glance

- Economical and compact recording of the energy demand
- Low investment risk through the use of existing automation technology
- Easy integration into the TIA Portal
- Energy management systems compliant with ISO 50001 and energy audits conforming to DIN EN 16247-1

#### Further information

- siemens.com/simatic-energiemanagement
- siemens.com/io-systems
- siemens.com/s7-1200

# Compact and economical recording in energy distribution systems

Thanks to its modular and compact design, the Energy Meter is a cost-effective solution for the recording of several outputs in an energy distribution system. The modules can not only be set up centrally on a SIMATIC S7-1200 or an ET 200SP CPU, but can also be set up on an ET 200SP IM on a distributed basis.

## Easy integration into TIA Portal and Energy Manager PRO

The Energy Meters can be easily commissioned in the TIA Portal. With the Energy Suite, the energy management program can be generated automatically and all energy data can be seamlessly transferred to the higher-level SIMATIC Energy Manager PRO energy management system.

Published by Siemens AG 2016

Digital Factory P.O. Box 48 48 90026 Nuremberg, Germany Article No.: DFFA-B10031-01-7600 Printed in Germany Dispo 06303 GB 160166 DB 04162.0 © 2016, Siemens AG Subject to changes and errors.
The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded